HUAHENG



Welding System


HUAHENG WELDING CO., LTD.








TOA50
Narrow spacing Tube to Tube
Welding Head





Technical Specification	
- 1 (
Tube OD (mm)	Ф32 ~ Ф51
Tungsten diameter (mm)	Ф3.2
Wire diameter (mm)	Ф1.0
Rotation speed (rpm)	0.25 ~ 5.02
Cooling	Water
Dimension (mm)	
Α	128
В	140
С	85 ~ 97
D	78
E	59
F	360
Weight (kg)	5



Brief Introduction

This welding head is special designed for tube to U–shape tube TIG welding, suitable for carbon steel, stainless steel tube to tube connection, mainly for wire feeding or self-fusion, integrated wire feeder with AVC & OSC function.

Support equipment: i-Arc400 Programmable Orbital Welding Power Source.


Application: chemical, food, engineering installation, boiler, military, nuclear and so on.


Features

- Special design for U-shape tube and narrow spacing tube to tube connection;
- Integrated orbital welding head and wire feeding;
- Unique cable hose twist;
- Motorized AVC and OSC motion for narrow spacing application;
- Quick launched clamping device to ensure homocentric;
- The most authorized practical experience ensures welding quality and repeatability.










HUAHENG



Add: No.1588 Boshi Road, Kunshan, Jiangsu, P.R. China. PC: 215347 Tel: +86(0)512-81866666 Fax: +86(0)512-57328188 www.huahengweld.com E-mail: info@huahengweld.com